



YAMAHA

OUTBOARD

ENDURO

ENDURO

«ENDURO» engines, absolute workhorses, offer unrivalled performance for your money and can withstand the toughest usage conditions.

All good reasons to explain why YAMAHA Enduro engines are used on the vast majority of traditional fishing boats for decades.



Output	8 cv	15cv	25 cv	40cv	60cv
Model	E8DMHS / E8DMHL	E15DMHS / E15DMHL	E25BMHS / E25BMHL	E40GMHL	E60 HMHDL
Engine transom height	S: 442mm L: 582mm	S: 442mm L: 569mm	S: 423mm L: 550mm	L: 571mm	L: 571mm
Displacement (cc)	165 cc	246 cc	496 cc	669 cc	849 cc
Engine type	L2	L2	L2	L2	L3
Compression ratio	6,8	7,0	6,2	6,25	6,1
Lubrication system	Pre-Mixing 2 %				
Fuel	Regular Gasoline				
Starter system	Manual	Manual	Manual	Manual	Manual
Steering / Control	Tiller handle	Tiller handle	Tiller handle	Tiller handle	Tiller handle + Hydro Trim and Tilt
Fuel consumption (l./h.)	4 l./h @ 5500 r/min	7,7 l./h @ 5500 r/min	10,7 l./h @ 5500 r/min	20 l./h @ 5500 r/min	25,5 l./h @5500 r/min
Dry weight (kg)	28 kg - 29 kg	38 kg - 40 kg	52 kg - 55,5 kg	65 kg - 68 kg	96 kg - 105 kg

Output	75cv	115cv	150 cv	200cv
Model	E75 BMHDL	E115 AETL	150 AETL / 150 AETX	200 AETL / 200 AETX
Engine transom height	L: 521mm	L: 515mm	L: 515mm X: 642mm	L: 515mm X: 642mm
Displacement (cc)	1140 cc	1730 cc	2596 cc	2596 cc
Engine type	L3	V4	V6	V6
Compression ratio	4,5	5,7	6,2	5,9
Lubrication system	Pre-Mixing 2 %			
Fuel	Regular Gasoline			
Starter system	Manual	Electric	Electric	Electric
Steering / Control	Tiller handle + Hydro Trim and Tilt	Remote control + Power Trim and Tilt	Remote control + Power Trim and Tilt	Remote control + Power Trim and Tilt
Fuel consumption (l./h.)	31 l./h @5500 r/min	47 l./h @5500 r/min	72 l./h @5500 r/min	81 l./h @5500 r/min
Dry weight (kg)	112 kg - 117 kg	147 kg - 160 kg	178 kg - 186 kg	178 kg - 186 kg